AR 332 - AR 520

High-efficient hardmount industrial washer-extractors

FEATURES

- Rigid mounted, normal spin- AR332 = 150G, AR520 = 100 G
- Stainless steel top panel, anthracite grey front and side panels
- Stainless steel drum and tub
- Basic control easy to use microprocessor
- Patented soap hopper
- High capacity water inlets
- Large drain valve (Ø76mm)
- Easy access to all vital parts from the front
- Large door opening for easy loading and unloading

OPTIONS

- Coin-operated timer (CPS)
- Stainless steel front and side panels
- USB plug (on the back panel)
- Liquid Soap Print liquid soap connection
- Liquid soap pumps
- Water recovery kit
- Steam heating version
- 3rd water inlet





DIMENSIONS & SPECIFICATIONS

HIGH-EFFICIENT HARDMOUNT INDUSTRIAL WASHER-EXTRACTORS

TYPE		AR332	AR520
INNERDRUM			
maximum capacity 1:9	kg	39	58
capacity 1:10	kg	35	52
volume	liters	332	520
diameter	mm	914	914
DRUM SPEED			
wash	rpm	38	38
extraction	rpm	440	440
G-FACTOR		150	100
HEATING			
electricity (standard)	kW	27	40,6
steam	bar	1 - 8	1 - 8
hot water	°C	90	90
Sound pressure level	dB (A)	<65	<65
Water valves connection	BSP	3/4"	1"
Water pressure	kPa	100-800	100-800
Rec. water pressure	kPa	300-500	300-500
Water inlet	l/min	66-188	183-518
Drain valve	outer Ø mm	2 x 76	2 x 76
Flow amount with drain valve	l/min	2 x 210	2 x 210
Steam valve connection	BSP	3/4"	3/4"
Steam pressure	kPa	100-800	100-800
TRANSPORT DATA			
Gross	kg	450	570
Net	kg	410	520
Packed HxWxD	mm	1700 x 1100 x 1385	1700 x 1100 x 1100

