

DC 8, DC 16

Drying Cabinet



FEATURES

- Very low energy consumption, only 0,5 kWh/kg, very short drying time, 42 minutes (DC 8)
- Four automatic programs and one program for time dry
- HTS - measures the level of humidity every single second, to determine exactly when the textiles are dry
- 16 m (DC 8), 32 m (DC 16) hanging length
- Double overheat-protection for increased security
- The top is removable for easier handling and installation
- Test program and error codes make it easier for maintenance
- Double sheet metal in sides and doors minimize loss of energy
- Hanging frame can be rotated 90° (DC 16), 180° (DC 8)
- Three fans (2 x DC 8) create perfect balance between evacuated and re-circulated air
- Service menu with possibilities to adjust the function of the cabinet
- CE approved

OPTIONS

- Single rack bar, instead of swinging rail
- Kit of 3 hook racks

DIMENSIONS & SPECIFICATIONS

DRYING CABINET

Model		DC 8	DC 16
Loading capacity	kg/lbs	up to 8 / 17,6	16
Drying capacity	g/min	62*	81**
Hanging length	m	16	32
Drying time	min	42*	64**
Evacuated air	m³/h	340 (max)	550
Heating effect	kW	6	9
Total effect	kW	6,3	9,45
Energy consumption / kg	kWh	0,5	0,54
ELECTRICAL CONNECTIONS			
Electrical connection (standard)		380-415V / 50-60Hz / 3ph + N	380-415V / 50-60Hz / 3ph + N
Total effect	kW	6,3	9,45
Heating elements	kW	6	9
AIR CONNECTIONS			
Outlet exhaust	ø mm	125	160
Outlet airflow	m³/h	230	300
Pressure drop	max Pa	70	260
SOUND LEVEL			
Airborne sound level	dB(A)	62	65
OPTIONAL ACCESSORIES			
Single bar	part number	POD131070	POD131070
Hook rack, set of three	part number	POD131071	POD131071
DIMENSIONS			
H x W x D	mm	1870 x 1200 x 640	1955 x 1800 x 800
SHIPPING DATA			
Net	kg	145	235
Gross (crate)	kg	159	275
Shipping volume	m³	1,78	1,76

* Drying of 6 kg cotton (dry weight), washed and high-spun to 43% residual moisture, dried to 0% residual moisture.

** Drying of 12 kg cotton (dry weight), washed and high-spun to 43% residual moisture, dried to 0% residual moisture.

