

LS 195

Industrial Tumble Dryer



FEATURES

- Standard stainless steel drum with large diameter
- Easy control - Easy to use microprocessor
- Combination of Radial and Axial airflow:
 - maximal heat transfer
 - low energy consumption
 - short drying time
- Large door opening for easy loading and unloading

OPTIONS

- Coin operated version
- Reversing drum
- Professional control - Full control
- Residual moisture control:
 - safe drying of delicate linen
 - humidity detection in %
 - ideal for dry cleaners, fire depts
 - available on Easy and Professional control

DIMENSIONS & SPECIFICATIONS

TUMBLE DRYERS

TYPE		LS 195
CAPACITY		
Capacity	kg/lb	9/20
Drum volume	l	190
Drum diameter	mm	Ø760
Number of drums		1
Number of loading doors		1
AIRFLOW		350
DRYING AVERAGE		0,150
MOTOR		
Fan	kW	0,75
Drive	kW	0,18
GAS HEATING		
Gas connection	inch	3/4"
Electrical connection		3×380-415V 50/60Hz, 3×220-240V 50Hz 3×208-240V 60Hz, 3×440V 60Hz
Energy	kW	12,5
	kBTU/h	42,7
ELECTRICAL HEATING		
Electrical connection		3×200-240V 50/60Hz, 3×380-415 50Hz, 3×380-415/440V 60Hz 3×208-240V 60Hz, 3×440V 60Hz, 3×480V 60Hz
Energy	kW	9/12
PROGRAMMER		
Easy control - antivandal (ECT)		Standard
Professional control (FCT)		Available
EXHAUST		Ø150
DIMENSIONS		
H×W×D	mm	1465×795×815
TRANSPORT DATA		
Gross weight	kg	180
Net weight	kg	170
Packing H×W×D	mm	1570×880×885
The data concerning dimensions of machines include all extended parts		

