

LSR33

Industrial Cylinder Heated Drying Ironers



FEATURES

- Large surface contact with linen over an angle of 300°
- Highly polished steel, thin cylinder
 - Reasonable price
 - Rapid response to temperature
 - Excellent thermal conductivity
- Emergency button and Main switch in one
- Finger protection bar for even more safety
- Durable Meta Aramid ironing belts
- Extra heavy press roller for high-quality ironing
- Patented direct drive
 - maintenance-free – system
- Patented central suction system with maintenance-free operation
- Automatic cool down
- Easy to operate microprocessor MCX
- Frequency controlled motor
- Indication of ironing speed and temperature
- Space-saving installation against the wall is possible: front return
- Exhaust outlet at back of the machine
- Electric or gas heating
- Metal fibre premix burner (for Gas only)
- Ergonomic design
- 3 temperature sensors
- Adjustable exhaust flap

OPTIONS

- Coin operated version
- Central payment system operated version (CPS)
- Chrome-plated cylinder for better thermal conduction and ironing quality
- Pedal of insert table stop system
- Exhaust output on the right
- Fixation set for mounting to the floor
- Auto adjustable ironing speed

DIMENSIONS & SPECIFICATIONS

INDUSTRIAL CYLINDER HEATED DRYING IRONERS

TYPE		LSR3316 E	LSR3320 E	LSR3316 G	LSR3320 G
ROLLER DIAMETER	mm	320	320	320	320
USEFUL ROLLER LENGHT	mm	1664	2080	1664	2080
CAPACITY*	kg/h	62	70	58	72
SPEED	m/min	1-6	1-6	1-6	1-6
HEATING					
Electric	kW	24.3	27.9		
Gas**	kW			25	30
MOTOR					
Roller motor	kW	0.18	0.18	0.18	0.18
Fan motor	kW		0,095 (50 Hz) / 0,125 (60 Hz)		
Total installed power	kW	24,7	28,3	0,5	0,5
Max. temperature	°C			180	
Consumption of electricity	kWh	21,4	27,3	0,5	0,5
Consumption of gas	m³/h			2,62	3,13
Gas types				G20, G25, G30, G31, G110	
Max. gas pressure	mbar			50	
Noise level	dB (A)			< 57	
Ingress protection				IP42	
ELECTRIC CONNECTION			380-415V 3AC+N 50/60 Hz 208-240V 3AC 50/60 Hz 380-415V 3AC-N 50/60 Hz		
		440V-480 3AC 60 Hz (1)		440V-480 3AC 60 Hz 208-240V 1AC 50/60 Hz	
DIMENSIONS					
HxWxD	mm	1110x2084x755	1110x2500x755	1110x2084x755	1110x2500x755
Netto weight	kg	435	490	410	465
Carton packing HxWxD	mm	1260x2190x800	1260x2610x800	1260x2190x800	1260x2610x800
Brutto weight	kg	485	560	465	540

* According to ISO 9398-1, ** For the G20, 20 mbar, (1) max. 456 V

