

LSR 80 – LSRA 80 – LSRP 80 – LSREP 80

Industrial Cylinder Heated Drying Ironers



FEATURES

- Large surface contact with linen
- Finger protection and emergency button for more safety
- Automatic cooldown
- Easy to operate microprocessor
- Indication of ironing speed and temperature
- Reverse mode possible
- Frequency controlled motor
- Space saving installation against the wall is possible: front return
- Electric, gas or steam heating
- 3 temperature sensors – Overheating check system

OPTIONS

- Front or rear return output
- Automatic feeding system
- Vacuum feeding table
- Model LSRA80 – Frontal and rear output
- Model LSRP80 – module R with length folding
- Model LSREP80 – ironer with feeding and length folding
- Module CS – cross folder and stacker (only for LSREP80)

CROSSFOLDER



STACKER



INDUSTRIAL CYLINDER HEATED DRYING IRONERS

TYPE		LSR80
ROLLER DIAMETER	mm	800
USEFUL ROLLER LENGHT	mm	3186
HEATING		
Electric heating	kW	75
Gas heating*	kW	110
Steam heating	kg/h	190
MOTOR		
Roller motor	kW	0,75
Fan motor	kW	2x 0,55/0,75 (50/60Hz)
Fan capacity	m3/h	2 x 1300
IRONING CAPACITY**	kg/h	195
ROLLER SPEED	m/min.	3-15 ***
ELECTRIC CONNECTION		380-415V 3AC + N 50/60Hz 208-240V 3AC 50/60Hz 380-415/440V 3AC (-N) 50/60Hz 440V 3 AC 60Hz
DIMENSIONS HxWxD	mm	1970x4260x1915
TRANSPORT DATA		
Net weight	kg	2610 - EI, 2480 - G, 2900 - S
Volume (crate packed)	m³	18,95
Crate packing HxWxD	mm	2080x4380x2080
* G20, 20 mbar		
** According to ISO 9398-1		
*** Max speed for length folding is 8 m/min		

